

MACLEAN SENIOR INDUSTRIES

PRODUCT BULLETIN



Manta Ray® Earth Anchor System

MacLean Senior Industries (MSI) is pleased to introduce the latest addition to our Earth Anchor product offering. The Manta Ray® Earth Anchor System is a "driven, tipping plate" soil anchor that has existed in the Communications Industry for over 30 years. The product was developed, patented, and sold under Foresight Products and recently acquired by MacLean Power Systems.



Features

- Designed to be installed in hard to reach places, not accessible by conventional auger trucks.
- Anchors proof loaded to exact capacity required during installation. No more guess work on holding strength!
- Fast, easy installation using lightweight, portable equipment.

US PATENT D572546 US PATENT #6237289 US PATENT #7534073

Ordering Information

- Anchor Model is a series designation only.
- When ordering, use the <u>Part Number</u> designation. For example: 20229-UT-II.

MANTA RAY® UTILITY ANCHOR SYSTEMS					
ANCHOR MODEL	PART NO.	DESCRIPTION ULTIMA CAPAC	ΛΤΕ	STANDARD PACK	PACK WEIGHT
MK-B	20031	for saturated/swamp/muskeg soils 40 kip	s	1	67.5 lbs.
MR-SR-UT-II	20229-UT-II	for loose or wet soils 40 kip	S	2	39.8 lbs.
MR-1-UT-II	20036-UT-II	for average/normal soils 40 kip	s	4	47.7 lbs.
MR-2-UT-II	20199-UT-II	for hard soils 40 kip	s	4	39.2 lbs.
MR-3-UT-II	20210-UT-II	for average/normal soils 20 kip	s	6	42.4 lbs.
MR-4-UT-II	20221-II	for average/normal soils 18 kip	s	6	31.1 lbs.
MANTA RAY SG DRIVE STEEL (COMPLETE SETS)					
		de shank, 3 couplers, 2 extensions, 1 drive tip, g	ad e	extractor bar, &	carrying bag
SGC-14	50243	For 1-1/4" x 6" chuck hammer/breakers		1 set	59.7 lbs
SGC-18	50244	For 1-1/8" x 6" chuck hammer/breakers			
Piece Parts For Drive Steel					
SG-14	50231	1-1/4" hex x 16" shank, 15-1/2" OAL		1	5.7 lbs.
SG-18	50232	1-1/8" hex x 6" shank, 15-1/2" OAL		1	4.9 lbs.
SG-2	50233	Drive Steel Extension piece -33"		1	11.5 lbs.
SG-3	50236	Radiused drive tip - 30"		1	10.5 lbs.
SG-4	50240	Drive steel coupler piece - Standard		1	2.9 lbs.
SG-4MD	51014	Drive steel coupler piece - Medium Duty		1	3.8 lbs.
SG-X	50242	Drive steel extractor bar		1	8.5 lbs.
GB-1	50084	Drive steel carrying bag		1	1.4 lbs.
ANCHOR LOCKERS					
LL-1	50127	Complete Anchor Locker Assembly Includes: base plate, hydraulic ram, control valve, holding capacity read out gauge, adapter setting bar for SAR style anchor rods, tapered jaws and carrying container. 20,000 lbs.maximum capacity.		1	159.0 lbs
HYDRAULIC POWER PACKS					
HB90-14CE	50364	Hydraulic Anchor Driving Hammer with 1-1/4" x chuck, 90# class	6"	1	88.0 lbs
HC-16-25	50087	25' Hydraulic Hose with HTMA II Coupler - minimum 2 required; use 4 for maximum versal	ility	1	8.0 lbs
GPU18-8CE	50382	Portable Hydraulic Power Unit 18-horsepower, 8 GPM, 2000 PSI, runs HB-90, LL-1, LB-1	5-	1	315.0 lbs